



# ATR PAINT MIXING ROOMS

Col-Met ATR Paint Mixing Rooms provide a clean, contaminant-free environment for paint preparation and mixing. Delivering optimal air circulation and filtration, our paint mixing rooms effectively remove air particulates that can negatively permeate paints being processed.

Unique only to Col-Met ATR paint mixing rooms, all units come standard with exhaust fans and chambers, an air intake plenum, and a control panel that is readily equipped with all necessary programming needed for efficient operations.

Achieve particulate-free paint mixes with Col-Met ATR paint mixing rooms.

## STANDARD ON ALL ATR MIXING ROOMS:

- 14" DIAMETER TUBEAXIAL EXHAUST FAN
- EXHAUST CHAMBERS
- AIR INTAKE PLENUM
- CONTROL PANEL EQUIPPED WITH NECESSARY PROGRAMMING
- PREMIUM 18-GAUGE STEEL, WHITE POWDERED-COATED FINISH
- BRIXON™ LATCHES ON DOOR OPENING
- 14" X 48" OBSERVATION WINDOW IN PERSONNEL DOORS



## COL-MET ATR PAINT MIXING ROOMS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Lights		Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Open	S&G		Dia.	HP	Int.	Exh.
PMR-0808	8'-0"	8'-0"	8'-0"	8'-4"	8'-2"	10'-6"	1 with Window	1	0	1930	14"	1/2 HP	4	2
PMR-0810	8'-0"	8'-0"	10'-0"	8'-4"	8'-2"	12'-6"	1 with Window	1	1	1930	14"	1/2 HP	4	2
PMR-0812	8'-0"	8'-0"	12'-0"	8'-4"	8'-2"	14'-6"	1 with Window	1	1	1930	14"	1/2 HP	4	2
PMR-0815	8'-0"	8'-0"	15'-0"	8'-4"	8'-2"	17'-6"	1 with Window	2	1	1930	14"	1/2 HP	4	2

Smooth and consistent in performance, air is drawn in through the filtered air intake plenum through the work area and into the exhaust chamber located in the lower opposite end of the room. The filtered exhaust air is then drawn through the exhaust plenum, making a clean discharge into the outside atmosphere through the exhaust stack and providing optimal ventilation.

ATR paint mixing rooms are equipped with four-tube, 48", 32-watt, fluorescent ceiling panel light fixtures that deliver full booth illumination and enhanced clarity. Each light is sealed behind clear tempered safety glass, and all fixtures are UL listed and approved for their intended use and placement.

Col-Met Spray Booth Products comply with all OSHA and NFPA regulations.



# ATR PAINT MIXING ROOMS

### COL-MET SPRAY BOOTHS

Dallas, TX // e-mail: [ATRgroup@colmetsb.com](mailto:ATRgroup@colmetsb.com)

Toll-free: 888.452.6684 // [www.colmetsb.com/ATR](http://www.colmetsb.com/ATR)

