

ATR TRUCK & LARGE EQUIPMENT BOOTHS

Col-Met ATR Truck and Large Equipment Booths can be designed and configured to fit your specific application needs. We have the capability to build custom systems for finishing trucks, construction equipment, recreational vehicles and other larger equipment efficiently and economically.

- **No more “oil canning” effect** with our use of more structurally sound steel. Improper handling, installation, or attachment to misaligned steel supports can cause “oil canning”.
- **5/16" bolts versus industry-standard 1/4" bolts** for tighter, more secure bolting. Our nut and bolt construction provides consistent structural stability and makes for simpler installation. Our booths can also be easily uninstalled and reinstalled if necessary.
- **Standard tri-fold doors have adjustable slotted-hole hinges, not weld-on ones**, making it much easier to position and install the booth doors.
- **Very installer-friendly booth construction** and design that offers you a substantial savings during installation - taking up to 25% less time to complete the job.




STEEL VERTICAL MEMBERS EVERY 10' FOR EVEN MORE STRUCTURAL SUPPORT. These members help allow the structure to accept standard manlifts without any upgrade or additional upcharge.



“ANYWHERE PLACEMENT” OF PERSONNEL DOORS AND LIGHT FIXTURES. Our 14Ga horizontal stiffeners running the entire length of our booth allow for specific placements of doors and lights to fit your particular application.



BRIGHT FULL BOOTH ILLUMINATION. Provided by UL listed, four-tube, 32-watt, fluorescent light fixtures that have been approved for their intended use and placement. Optional inside access light fixtures are also available.



THE FIT AND FINISH. Entire structure is powder-coated with our standard TGIC polyester gloss white for a professional and impressive look. Fit for function—the perfect booth for you.

COL-MET ATR TRUCK & LARGE EQUIPMENT BOOTHS

CLASSIC CROSSDRAFT TRUCK & LARGE EQUIPMENT BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
TCC34SB	16'-0"	16'-0"	34'-0"	17'-0"	16'-6"	34'-4"	1	11'-4"	13'-10.5"	1	Filter	2	22	24	25,600	42"	7.5 HP	48	48
TCC34RF	16'-0"	16'-0"	34'-0"	17'-0"	16'-6"	34'-4"	1	11'-4"	13'-10.5"	1	Solid	2	22	24	25,600	42"	7.5 HP	48	48
TCC34DT	16'-0"	16'-0"	34'-0"	17'-0"	16'-6"	34'-4"	1	11'-4"	13'-10.5"	2	1 of ea.	2	22	24	25,600	42"	7.5 HP	48	48
TCC44SB	16'-0"	16'-0"	44'-0"	17'-0"	16'-6"	44'-4"	2	11'-4"	13'-10.5"	1	Filter	4	28	32	25,600	42"	7.5 HP	48	48
TCC44RF	16'-0"	16'-0"	44'-0"	17'-0"	16'-6"	44'-4"	2	11'-4"	13'-10.5"	1	Solid	4	28	32	25,600	42"	7.5 HP	48	48
TCC44DT	16'-0"	16'-0"	44'-0"	17'-0"	16'-6"	44'-4"	2	11'-4"	13'-10.5"	2	1 of ea.	4	28	32	25,600	42"	7.5 HP	48	48
TCC54SB	16'-0"	16'-0"	54'-0"	17'-0"	16'-6"	54'-4"	3	11'-4"	13'-10.5"	1	Filter	6	34	40	25,600	42"	7.5 HP	48	48
TCC54RF	16'-0"	16'-0"	54'-0"	17'-0"	16'-6"	54'-4"	3	11'-4"	13'-10.5"	1	Solid	6	34	40	25,600	42"	7.5 HP	48	48
TCC54DT	16'-0"	16'-0"	54'-0"	17'-0"	16'-6"	54'-4"	3	11'-4"	13'-10.5"	2	1 of ea.	6	34	40	25,600	42"	7.5 HP	48	48
TCC64SB	16'-0"	16'-0"	64'-0"	17'-0"	16'-6"	64'-4"	4	11'-4"	13'-10.5"	1	Filter	8	40	48	25,600	42"	7.5 HP	48	48
TCC64RF	16'-0"	16'-0"	64'-0"	17'-0"	16'-6"	64'-4"	4	11'-4"	13'-10.5"	1	Solid	8	40	48	25,600	42"	7.5 HP	48	48
TCC64DT	16'-0"	16'-0"	64'-0"	17'-0"	16'-6"	64'-4"	4	11'-4"	13'-10.5"	2	1 of ea.	8	40	48	25,600	42"	7.5 HP	48	48

MODIFIED DOWNDRAFT TRUCK & LARGE EQUIPMENT BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
TSC34SB	16'-0"	16'-0"	34'-0"	17'-0"	18'-6"	34'-4"	1	11'-4"	13'-10.5"	1	Solid	2	22	24	25,600	42"	7.5 HP	48	48
TSC34RF	16'-0"	16'-0"	34'-0"	17'-0"	18'-6"	34'-4"	1	11'-4"	13'-10.5"	1	Solid	2	22	24	25,600	42"	7.5 HP	48	48
TSC34DT	16'-0"	16'-0"	34'-0"	17'-0"	18'-6"	34'-4"	1	11'-4"	13'-10.5"	2	Solid	2	22	24	25,600	42"	7.5 HP	48	48
TSC44SB	16'-0"	16'-0"	44'-0"	17'-0"	18'-6"	44'-4"	2	11'-4"	13'-10.5"	1	Solid	4	28	32	25,600	42"	7.5 HP	48	48
TSC44RF	16'-0"	16'-0"	44'-0"	17'-0"	18'-6"	44'-4"	2	11'-4"	13'-10.5"	1	Solid	4	28	32	25,600	42"	7.5 HP	48	48
TSC44DT	16'-0"	16'-0"	44'-0"	17'-0"	18'-6"	44'-4"	2	11'-4"	13'-10.5"	2	Solid	4	28	32	25,600	42"	7.5 HP	48	48
TSC54SB	16'-0"	16'-0"	54'-0"	17'-0"	18'-6"	54'-4"	3	11'-4"	13'-10.5"	1	Solid	6	34	40	25,600	42"	7.5 HP	48	48
TSC54RF	16'-0"	16'-0"	54'-0"	17'-0"	18'-6"	54'-4"	3	11'-4"	13'-10.5"	1	Solid	6	34	40	25,600	42"	7.5 HP	48	48
TSC54DT	16'-0"	16'-0"	54'-0"	17'-0"	18'-6"	54'-4"	3	11'-4"	13'-10.5"	2	Solid	6	34	40	25,600	42"	7.5 HP	48	48
TSC64SB	16'-0"	16'-0"	64'-0"	17'-0"	18'-6"	64'-4"	4	11'-4"	13'-10.5"	1	Solid	8	40	48	25,600	42"	7.5 HP	48	48
TSC64RF	16'-0"	16'-0"	64'-0"	17'-0"	18'-6"	64'-4"	4	11'-4"	13'-10.5"	1	Solid	8	40	48	25,600	42"	7.5 HP	48	48
TSC64DT	16'-0"	16'-0"	64'-0"	17'-0"	18'-6"	64'-4"	4	11'-4"	13'-10.5"	2	Solid	8	40	48	25,600	42"	7.5 HP	48	48

FULL DOWNDRAFT TRUCK & LARGE EQUIPMENT BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
TDD30SB	16'-0"	16'-0"	30'-0"	17'-0"	18'-6"	30'-4"	1	11'-4"	13'-10.5"	1	Solid	2	22	24	24,000	42"	7.5 HP	48	30
TDD30DT	16'-0"	16'-0"	30'-0"	17'-0"	18'-6"	30'-4"	1	11'-4"	13'-10.5"	2	Solid	2	22	24	24,000	42"	7.5 HP	48	30
TDD40SB	16'-0"	16'-0"	40'-0"	17'-0"	18'-6"	40'-4"	2	11'-4"	13'-10.5"	1	Solid	4	28	32	32,000	(2)42"	5 HP	64	40
TDD40DT	16'-0"	16'-0"	40'-0"	17'-0"	18'-6"	40'-4"	2	11'-4"	13'-10.5"	2	Solid	4	28	32	32,000	(2)42"	5 HP	64	40
TDD50SB	16'-0"	16'-0"	50'-0"	17'-0"	18'-6"	50'-4"	3	11'-4"	13'-10.5"	1	Solid	6	34	40	40,000	(2)42"	5 HP	80	50
TDD50DT	16'-0"	16'-0"	50'-0"	17'-0"	18'-6"	50'-4"	3	11'-4"	13'-10.5"	2	Solid	6	34	40	40,000	(2)42"	5 HP	80	50
TDD60SB	16'-0"	16'-0"	60'-0"	17'-0"	18'-6"	60'-4"	4	11'-4"	13'-10.5"	1	Solid	8	40	48	48,000	(2)42"	7.5 HP	96	60
TDD60DT	16'-0"	16'-0"	60'-0"	17'-0"	18'-6"	60'-4"	4	11'-4"	13'-10.5"	2	Solid	8	40	48	48,000	(2)42"	7.5 HP	96	60

SIDE DOWNDRAFT TRUCK & LARGE EQUIPMENT BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
TSD30SB	16'-0"	16'-0"	30'-0"	21'-4"	18'-6"	30'-4"	1	11'-4"	13'-10.5"	1	Solid	2	22	24	24,000	(2)30"	3 HP	46	46
TSD30DT	16'-0"	16'-0"	30'-0"	21'-4"	18'-6"	30'-4"	1	11'-4"	13'-10.5"	2	Solid	2	22	24	24,000	(2)30"	3 HP	46	46
TSD40SB	16'-0"	16'-0"	40'-0"	21'-4"	18'-6"	40'-4"	2	11'-4"	13'-10.5"	1	Solid	4	28	32	32,000	(4)24"	2 HP	60	60
TSD40DT	16'-0"	16'-0"	40'-0"	21'-4"	18'-6"	40'-4"	2	11'-4"	13'-10.5"	2	Solid	4	28	32	32,000	(4)24"	2 HP	60	60
TSD50SB	16'-0"	16'-0"	50'-0"	21'-4"	18'-6"	50'-4"	3	11'-4"	13'-10.5"	1	Solid	6	34	40	40,000	(4)30"	2 HP	76	76
TSD50DT	16'-0"	16'-0"	50'-0"	21'-4"	18'-6"	50'-4"	3	11'-4"	13'-10.5"	2	Solid	6	34	40	40,000	(4)30"	2 HP	76	76
TSD60SB	16'-0"	16'-0"	60'-0"	21'-4"	18'-6"	60'-4"	4	11'-4"	13'-10.5"	1	Solid	8	40	48	48,000	(4)30"	3 HP	90	90
TSD60DT	16'-0"	16'-0"	60'-0"	21'-4"	18'-6"	60'-4"	4	11'-4"	13'-10.5"	2	Solid	8	40	48	48,000	(4)30"	3 HP	90	90

18' AND 20' WIDE MODELS ALSO AVAILABLE

COL-MET SPRAY BOOTHS

Dallas, TX // e-mail: ATRgroup@colmetsb.com

Toll-free: 888.452.6684 // www.colmetsb.com/ATR

